

Model Name:

Elite Monitored PDU **Adv.**

Elite Monitored PDU provides user to monitor the total power usage information of PDU from the remote end through the Internet to fully understand the power consumption of all the devices. Set up overload event alerts and notify managers via Email and TRAP, allowing managers to respond to crises in the shortest possible time to minimize disasters.

The PDU has environmental sensor ports that track climate information: temperature and humidity environment variables. The data is available from any web browser and is SNMP-compliant for easy tracking of critical data without the use of any external software.

Provide central management software, which can manage a large number of PDUs' power, temperature and humidity information. The database stores the power consumption information of the power strip and provides the history curve chart for the manager's reference.

It provides an advanced function which is to manage up to 8 PDUs by a single IP address. It means administrators can monitor and control multiple PDUs through one web interface.

Features:

System Function:

- **Embedded system:**
Support Ethernet interface, provides webpage and SNMP remote management.
 - **Local display information:**
OLED can display current, voltage, kWh, IP, temperature and humidity information.
 - **Multiple protocols:**
Support ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, HTTPS, FTP, NTP, SNMP v1/2/3, TLS1.2, IPv4 and IPv6, Telnet, SSHv2
 - **Management Account Certification:**
Radius certification support.
 - **Multi-account management:**
Multi-group account management system. And provide three-tier permission management.
 - **IP filtering:**
Support IP filtering, improve network security mechanisms.
 - **Power record:**
Store up to 100000 power and event data.
 - **Daisy Chain:**
Support cascading management
 - **Hot-Swap:** the replacement of network module without shutting down the PDU
 - **Remote firmware upgrade:**
Provides remote firmware upgrade mechanism.
 - **System operation message:**
Send the normal operation of the message automatically by trap.
 - **Hardware key definition:**
User-definable button function.
 - **Temperature unit conversion:**
Temperature units can choose Celsius or Fahrenheit
 - **System configuration restore:**
Support the output of the system settings, to easily deploy a large amount of the same model of PDU.
 - **Multilingual Support:**
Support Chinese, English, French, German, Spanish, Russian, Czech, Arabian, Persian.
 - **USB Option:**
Support external USB network card, support wireless network
-

Power Management:



Remote Monitor

Remote monitoring PDU status by web and SNMP



kWh Measurement

Voltage, frequency, power factor, active power, apparent power and kWh measurement.



Current Measurement

Measure PDU total current consumption.



Mail Notification

Notify specified user by mail and SNMP when outlet action or current over threshold.



Threshold Sensing

User-definable warning and overload threshold value as the basis for alarm.



Event Alert

When current exceeds the preset threshold, PDU will beep and LED will flash.



Overload Protection

When overload, circuit breaker will automatically trip to protect the safety of electricity.



Central Management

Free centralized monitoring software, real-time monitoring of a large number of PDU, provide data records and history chart.



Environment Detection

Optional accessory probe to detect temperature and humidity.



Circuit Breaker Detection

PDU can detect whether breaker is tripped due to the power event. Display and notify the manager of breaker status accordingly

Model Number:

WML-1623K-16N1



Specification

| Output | | Input | |
|---------------------|--|--------------------|----------------------------|
| Voltage | 200-240 VAC | Voltage | 200-240 VAC |
| Max. Current | 16 A | Frequency | 50/60Hz, full range |
| Outlet | (14) C13, (2) C19 | Max. Capacity | 3840 VA |
| Overload Protection | (1) 16A UL1077 breaker | Connection | C20, Detachable Power cord |
| | | Status Ind. | (1) Red LED |
| Measurement | | Other | |
| Current | +/- 1%+/-0.1A @0.2A ~ 32 A | ENET Connection | (1) RJ45 |
| Voltage | +/- 1% +/- 1V @80V~250V | ENV Connection | (1) RJ11 |
| Active Power | +/- 1% +/- 5W @50W~8000W | Function Selection | (1) Button |
| Apparent Power | +/- 1% @50VA~8000VA | Daisy Chain | (2) RJ22 |
| Frequency | +/- 1% @50~65Hz | WIFI Ready | (1) USB |
| Power Factor | +/- 1% @0.1~1.0 | Info. Display | Monochrome OLED |
| kWh | .001kWh~99999.999kWh, (+/- 1% @50W~8000W) kh=1.0 | | |
| Dimension/Weight | | Operation | |
| Net Size | 1245 x 56 x 80 mm | Operation Temp. | 0 ~ 50°C |
| Net Weight | 3.8 kg | Operation Humid. | 0% ~ 95% RH |
| Package Size | 1360 x 220 x 110 mm | Storage Temp. | -20°C ~ 65°C |
| Package Weight | 4.8 kg | Storage Humid. | 0% ~ 95% RH |
| Approval | | | |
| Certification | CE | | |
| Warranty | 2 years | | |

Package

| No. | Description |
|-----|-------------------------------------|
| 1 | PDU 1 set |
| 2 | Rack mount accessories 2 sets |
| 3 | Power cord, C19 to C20, 3 m |
| 4 | Software, manual, MIB by link below |



Optional Accessory


| Model Number | Model Name |
|--------------|-----------------------|
| CPM-ENV-2 | Temp./Humidity probe |
| STR-C14-B | C13 socket protection |
| CPM-USB-1 | USB WIFI Dongle |



Line Drawing



44.00



1245.00

56.00