

Model Name:

Elite Monitored PDU

Elite Monitored PDU provides user to monitor the total power usage information of PDU from the remote end through the Internet to fully understand the power consumption of all the devices. Set up overload event alerts and notify managers via Email and TRAP, allowing managers to respond to crises in the shortest possible time to minimize disasters.

The PDU has environmental sensor ports that track climate information: temperature and humidity environment variables. The data is available from any web browser and is SNMP-compliant for easy tracking of critical data without the use of any external software.

Provide central management software, which can manage a large number of PDUs' power, temperature and humidity information. The database stores the power consumption information of the power strip and provides the history curve chart for the manager's reference.

Features:

System Function:

- **Embedded system:**
Support 10/100M Ethernet interface, provides webpage and SNMP remote management.
- **Local display information:**
Seven-segments can display current, IP address and temperature and humidity values.
- **Multiple protocols:**
Support ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, HTTPS, FTP, NTP, SNMP v1/2/3, TLS1.2, IPv4 and IPv6, Telnet, SSHv2
- **Management Account Certification:**
Radius certification support.
- **Multi-account management:**
Multi-group account management system. And provide three-tier permission management.
- **IP filtering:**
Support IP filtering, improve network security mechanisms.
- **Power record:**
Store up to 100000 power and event data.
- **Remote firmware upgrade:**
Provides remote firmware upgrade mechanism.
- **System operation message:**
Send the normal operation of the message automatically by trap.
- **Hardware key definition:**
User-definable button function.
- **Temperature unit conversion:**
Temperature units can choose Celsius or Fahrenheit
- **System configuration restore:**
Support the output of the system settings, to easily deploy a large amount of the same model of PDU.
- **Multilingual Support:**
Support Chinese, English, French, German, Spanish, Russian, Czech, Arabian, Persian.

Power Management:



Remote Monitor

Remote monitoring PDU status by web and SNMP



kWh Measurement


Voltage, frequency, power factor, active power, apparent power and kWh measurement.



CURRENT MEASUREMENT

Current Measurement

Measure PDU total current consumption.



THRESHOLD SENSING

Threshold Sensing

User-definable warning and overload threshold value as the basis for alarm.



OVERLOAD PROTECTION

Overload Protection

When overload, circuit breaker will automatically trip to protect the safety of electricity.



ENVIRONMENT DETECTION

Environment Detection

Optional accessory probe to detect temperature and humidity.



MAIL NOTIFICATION

Mail Notification

Notify specified user by mail and SNMP when outlet action or current over threshold.



EVENT ALERT

Event Alert

When current exceeds the preset threshold, PDU will beep and LED will flash.



CENTRAL MANAGEMENT

Central Management

Free centralized monitoring software, real-time monitoring of a large number of PDU, provide data records and history chart.



Breaker Detection

Circuit Breaker Detection

PDU can detect whether breaker is tripped due to the power event. Display and notify the manager of breaker status accordingly

Model Number:

WMC-1511A-16N1



Plug



Specification

| Output | | Input | |
|---------------------|--|--------------------|------------------------------|
| Voltage | 100-127 VAC | Voltage | 100-127 VAC |
| Max. Current | 15 A | Frequency | 50/60Hz, full range |
| Outlet | (16) 5-15/20R | Max. Capacity | 1905 VA |
| Circuit Ind. | (1) Red LED | Connection | 5-15P, Detachable Power cord |
| Overload Protection | (1) 15A UL1077 breaker | | |
| Measurement | | Other | |
| Current | +/- 1% +/- 0.1A @0.2A ~ 32 A | ENET Connection | (1) RJ45 |
| Voltage | +/- 1% +/- 1V @80V~250V | ENV Connection | (1) RJ11 |
| Active Power | +/- 1% +/- 5W @50W~8000W | Function Selection | (1) Button |
| Apparent Power | +/- 1% @50VA~8000VA | DHCP Ind. | (1) Green LED |
| Frequency | +/- 1% @50~65Hz | SSL Ind. | (1) Blue LED |
| Power Factor | +/- 1% @0.1~1.0 | Info. Display | 4 digits of 7 Segments |
| kWh | .001kWh~99999.999kWh, (+/- 1% @50W~8000W) kh=1.0 | | |
| Dimension/Weight | | Operation | |
| Net Size | 1245 x 56 x 80 mm | Operation Temp. | 0 ~ 50°C |
| Net Weight | 3.8 kg | Operation Humid. | 0% ~ 90% RH |
| Package Size | 1360 x 220 x 110 mm | Storage Temp. | -20°C ~ 65°C |
| Package Weight | 4.8 kg | Storage Humid. | 0% ~ 90% RH |
| Approval | | | |
| Certification | FCC | | |
| Warranty | 2 years | | |


Package

Optional Accessory


| No. | Description | Model Number | Model Name |
|-----|-------------------------------------|--------------|----------------------|
| 1 | PDU 1 set | CPM-ENV-2 | Temp./Humidity probe |
| 2 | Rack mount accessories 2 sets | | |
| 3 | C19 to 5-15P, power cord 3m | | |
| 4 | Software, manual, MIB by link below | | |



Line Drawing



44.00



56.00