

## Model Name:

### Basic PDU

## Features:

### Power Management:



#### Overload Protection

When overload, circuit breaker will automatically trip to protect the safety of electricity.

### Power Management Upgrade: (Works with CPM, the following are CPM functions)



#### Remote Monitor

Remote monitoring PDU status by web and SNMP



#### Threshold Sensing

User-definable warning and overload threshold value as the basis for alarm.



#### Environment Detection

Optional accessory probe to detect temperature and humidity. (available by model)



#### Mail Notification

Notify specified user by mail and SNMP when outlet action or current over threshold.



#### Central Management

Free centralized monitoring software, real-time monitoring of a large number of PDU, provide data records and history chart.

## Model Number: PBH-3240C-06N6

Front view



Back view



Plug



## Specification

<b>Output</b>		<b>Input</b>	
Voltage	200-240 VAC	Voltage	400 VAC, 3 Phase 3P+N+PE
Max. Current	32 A / phase	Frequency	50/60Hz, full range
Outlet	(6) C19	Max. Capacity	22 kVA
Overload Protection	(6) 16A UL489 breaker	Connection	IEC309, power cord, 3m
<b>Measurement</b>		<b>Other</b>	
None		None	
<b>Dimension/Weight</b>		<b>Operation</b>	
Net size	432 x 216 x 44.5 mm	Operation Temp.	0 ~ 45°C
Net weight	4.0 kg	Operation Humid.	0% ~ 90% RH
Package Size	490 x 330 x 155 mm	Storage Temp.	-20°C ~ 65°C
Package Weight	4.6 kg	Storage Humid.	0% ~ 90% RH
<b>Approval</b>			
Certification	CE		
Warranty	2 years		

## Package

No.	Description.
1	PDU 1 set
2	Rack mount accessories 1 set
3	Manual by link below



## Optional Accessory

Model Number	Model Name
STR-C14-B	C13 socket protection



## Line Drawing

