

Model Name:

Intelligent 4 DI/DO Manager

The manager provides DIDO function. Users can remotely connect any type of sensor, including smoke detection, water detection, flow detection, access control, proximity switches and other sensors to determine the environmental status. When the status changes, set event alarms and notify managers via e-mail and SNMP TRAP, so that managers can respond to crises in the shortest time to minimize disasters.

The manager also has a temperature and humidity sensor interface, which can add a set of sensors to track temperature and humidity data.

Provide management software, which can manage a large number of environmental managers at the same time, store data in the database, and provide historical curve charts for reference.

Features:

System Function:

- Embedded system:
Support 10/100M Ethernet interface, provides webpage and SNMP remote management.
- Multiple protocols:
Support ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, HTTPS, FTP, NTP, SNMP v1/2/3, TLS1.2, IPv4 and IPv6, Telnet, SSHv2
- Management Account Certification:
Radius certification support.
- Multi-account management:
Multi-group account management system. And provide three-tier permission management.
- IP filtering:
Support IP filtering, improve network security mechanisms.
- Power record:
Store up to 100000 power and event data.
- Remote firmware upgrade:
Provides remote firmware upgrade mechanism.
- System operation message:
Send the normal operation of the message automatically by trap.
- Hardware key definition:
User-definable button function.
- Temperature unit conversion:
Temperature units can choose Celsius or Fahrenheit
- System configuration restore:
Support the output of the system settings, to easily deploy a large amount of the same model of PDU.
- Multilingual Support:
Support Chinese, English, French, German, Spanish, Russian, Czech, Arabian, Persian.

Power Management:



Remote Monitor

Remote monitoring device status by web and SNMP



Remote Control

Remote DO on/off by web and SNMP.



Digital I/O Support

Digital I/O

Connect various sensors. Support web pages to set various actions.



MAIL NOTIFICATION

Mail Notification

Notify specified user by mail and SNMP when DO action or current over threshold.



SCHEDULE CONTROL

Schedule Control

Timed & scheduled on/off/reboot control.



EVENT REACTION

Event Reaction

DO action via pre-set event, including power, environment event and receiving trap from other device.



PING EVENT CONTROL

Ping Event Control

When the specified IT device does not respond to PING, the output will perform a preset power action.



ENVIRONMENT DETECTION

Environment Detection

Optional accessory probe to detect temperature and humidity.



POWER SEQUENCE

Power Sequence

User-definable DO on/off sequence time.

Model Number:

IOT-IO-04J



Specification

Input		Other	
Voltage	100VAC-240VAC	ENET Connection	(1) RJ45
Connection	C14 Inlet	ENV Connection	(2) RJ11
Power Status	(1) Red LED	Function Selection	(1) Button
		DHCP Ind.	(1) Green LED
		SSL Ind.	(1) Blue LED
		Info. Display	4 digits of 7 Segments
DI		DO	
Type: Dry contact 1 set of 4-way terminal block. Connection: 0.5 to 1.5 mm ² / 28 to 14AWG Close status: Impedance less than 50 ohms Open status: Impedance greater than 50 ohms		Type: Relay 1 set of 4-way terminal block. Connection: 0.5 to 2.5 mm ² / 24 to 12 AWG Range : Contact Open(off) or Close (on) Rated load: 16A 240VAC / 16A 24Vdc Max. switching current: 16A Max. switching voltage: 250VAC Max. switching capacity: 4000VA	
Dimension/Weight		Operation	
Net Size	210 x110 x 56 mm	Operation Temp.	0 ~ 50°C
Net Weight	1 kg	Operation Humid.	0% ~ 90% RH
Package Size	TBD	Storage Temp.	-20°C ~ 65°C
Package Weight	TBD	Storage Humid.	0% ~ 90% RH
Approval			
Warranty	2 years		

Package

No.	Description
1	PDU 1 set
2	Power cord, C13 to C14, 1.8 m



3	Manual, MIB by link below
---	---------------------------



Line Drawing

